



## Declaration of performance no/ RGP000-DWU-117

- Unique identification code of the product-type: **SALISBURY (BLU T)**
- Type, batch or serial number: **SALISBURY (BLU T)**  
See label of the product.
- Article purpose: **For heating of interiors, for water central heating in closed systems without corrosive agents**
- Name, registered trade name or registered trade mark and contact address of the manufacturer: **Terma Sp. z o.o.  
Czaple 100  
PL 80-298 Gdańsk  
Poland  
www.termagroup.pl**
- Name and contact address of the authorised representative: **N/A**
- System or systems of assessment and verification of constancy of performance of the construction product: **System 3**
- In case of the declaration of performance concerning a construction product covered by a harmonised standard: **Instytut Energetyki, Oddział Techniki Grzewczej i Sanitarnej, Radom/Poland  
Determination of the product-type on the basis of type testing based on sampling carried out by the manufacturer.  
Report nr. NB1452/CPR/181/14  
  
Raport of corrosion examination no. 5097/C/1/98 (PN-EN 442-1:2015-02;p. 5.9)  
  
EN\_11210661-01 paint data sheet (PN-EN 442-1:2015-02; p. 4.4)**
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **N/A**
- Declared performance:**

Essential characteristics	Performance	Harmonised technical specification
Height A	A±2 mm; A: see Table 1	PN-EN 442-2:2015-02
Width B	B±2 mm; B: see Table 1	PN-EN 442-2:2015-02
Connection	G ½"	PN-EN ISO 228-2:2005
Resistance to separation of coating from substrate	[0]	PN-EN ISO 2409:2008
Max operating pressure	800 kPa	PN-EN 442-1:2015-02
Pressure tightness	1040 kPa	PN-EN 442-1:2015-02
Resistance to pressure	1352 kPa	PN-EN 442-1:2015-02
Max operating temperature	95 °C	PN-EN 442-1:2015-02
Surface condition	Radiator doesn't have any sharp edges.	PN-EN 442-1:2015-02

TERMA Sp. z o.o. ///  
 Czaple 100 | 80-298 Gdańsk | T: +48 58 / 694 05 55 | F: +48 58 / 694 05 56 | terma@termagroup.pl | www.termagroup.pl ///  
 NIP: 583-10-18-844 | REGON: 190558447 | nr rej. GIOŚ: E0001379W | Sąd Rej. w Gdańsku, VIII Wydz. Gosp. | KRS nr 0000069067 | kapitał zakładowy 2 360 500 PLN  
 konto: ING Bank Śląski S.A. 88 1050 1764 1000 0023 0692 5997 ///

PRODUKTY GRZEWCZE //// PRODUKTY MECHANICZNE //// PRODUKTY MEDYCZNE //// USŁUGI PRZEMYSŁOWE

Reaction to Fire	Class A1	PN-EN 442-1:2015-02
Durability Test- Humidity	Pass	PN-EN 442-1:2015-02
Release of dangerous substances	Pass	PN-EN 442-1:2015-02
Rated thermal output at 75/65/20	See Table 1	PN-EN 442-2:2015-02
Thermal output at different conditions	$\emptyset = K * \Delta T^n$ ; K, n see Table 1	PN-EN 442-2:2015-02

Name	Colour	Height A	Width B	Output 75/65/20	BTU 75/65/20	K	n
SALISBURY 700/440	PAINT	700	440	318	1085	2,56	1,2325
SALISBURY 700/540	PAINT	700	540	447	1525	3,0930	1,2325
SALISBURY 1030/440	PAINT	1030	440	435	1484	3,4970	1,2330
SALISBURY 1030/540	PAINT	1030	540	529	1805	4,2498	1,2339
SALISBURY 1030/640	PAINT	1030	640	621	2119	4,9878	1,2332
SALISBURY 1360/300	PAINT	1360	300	386	1317	3,0992	1,2333
SALISBURY 1360/440	PAINT	1360	440	552	1884	4,4320	1,2333
SALISBURY 1360/540	PAINT	1360	540	674	2300	5,4115	1,2333
SALISBURY 1360/640	PAINT	1360	640	795	2713	6,3828	1,2333
SALISBURY 1635/440	PAINT	1635	440	650	2218	5,2150	1,2335
SALISBURY 1635/540	PAINT	1635	540	794	2709	6,3683	1,2335
SALISBURY 1635/640	PAINT	1635	640	940	3207	7,5420	1,2335

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Czaple, 2016-06-29

Alina Zdybel  
Menedżer Produktu  
Zarządzanie Produktem – Produkty Profilowe

